



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

### SECTION 1: Identification

- 1.1 Product identifier**  
Trade name **A10 Pure Polish**
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**  
Relevant identified uses Vehicle polishing compound
- 1.3 Details of the supplier of the safety data sheet**  
B&B Blending, LLC  
10963 Leroy Drive  
Northglenn  
CO 80233  
United States
- telephone  
1.800.875.6320, 1.303.289.6320  
e-mail: info@bbblending.com  
website  
bbblending.com  
e-mail (competent person) Btirrell@bbblending.com  
(Beth Tirrell)
- 1.4 Emergency telephone number**  
Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500  
24 hour emergency number

### SECTION 2: Hazard(s) identification

- 2.1 Classification of the substance or mixture**  
Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard state-ment
A.4S	Skin sensitization	1	Skin Sens. 1	H317

For full text of abbreviations: see SECTION 16

- 2.2 Label elements**  
Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Signal word Warning

Pictograms

GHS07



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

### Hazardous ingredients for labelling

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)

### 2.3 Other hazards

Special danger of slipping by leaking/spilling product.

#### Hazards not otherwise classified

Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

#### Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture).

### 3.2 Mixtures

#### Description of the mixture

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
distillates (petroleum) hydro-treated, light	CAS No 64742-47-8	20 - < 40	Asp. Tox. 1 / H304	
odorless mineral spirits	CAS No 64742-48-9	1 - < 3	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
polyethylene glycol (5) undecyl ether	CAS No 34398-01-1	1 - < 3	Acute Tox. 4 / H302	
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)	CAS No 55965-84-9	< 0.1	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Skin Sens. 1 / H317	

For full text of abbreviations: see SECTION 16

## SECTION 4: First-aid measures

### 4.1 Description of first- aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray. BC-powder. Carbon dioxide (CO<sub>2</sub>).

#### Unsuitable extinguishing media

Water jet.

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>). Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Remove persons to safety.

#### For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

#### Advices on how to contain a spill

Covering of drains.

#### Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). collect spillage

sawdust

kieselgur (diatomite)

sand

universal binder

#### Appropriate containment techniques

Use of adsorbent materials.

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Recommendations

##### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

##### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Control of the effects

##### Protect against external exposure, such as

Frost.

#### 7.3 Specific end use(s)

See section 16 for a general overview.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
US	alpha-Alumina	1344-28-1	REL					NIOSH REL
US	alpha-alumina	1344-28-1	PEL		15			29 CFR 1910.1000
US	alpha-alumina	1344-28-1	PEL		5			29 CFR 1910.1000
US	aluminium oxide	1344-28-1	PEL (CA)		10			Cal/OSHA PEL
US	aluminium oxide	1344-28-1	PEL (CA)		5			Cal/OSHA PEL
US	glycerine	56-81-5	REL					NIOSH REL
US	glycerol	56-81-5	PEL		15			29 CFR 1910.1000
US	glycerol	56-81-5	PEL		5			29 CFR 1910.1000
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2,000			29 CFR 1910.1000

##### Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

#### 8.2 Exposure controls

##### Appropriate engineering controls

General ventilation.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

### Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.

#### Skin protection

#### Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	Liquid Viscous
Color	Light grey
Odor	Characteristic

#### Other safety parameters

PH (value)	Not determined
Melting point/freezing point	Not determined
Initial boiling point and boiling range	100 °C
Flash point	>100 °C at 101.3 kPa >212 °C at 1 atm
Evaporation rate	Not determined
Flammability (solid, gas)	Not relevant Fluid

#### Explosive limits

Lower explosion limit (LEL)	0.6 vol%
Upper explosion limit (UEL)	19 vol%



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

<b>Vapor pressure</b>	31.69 hPa at 25 °C
<b>Density</b>	1.011 g/ml at 25 °C
<b>Vapor density</b>	This information is not available
<b>Relative density</b>	1.011 at 25 °C (water = 1)
<b>Solubility(ies)</b>	Not determined

### Partition coefficient

<b>- n-octanol/water (log KOW)</b>	This information is not available
<b>Auto-ignition temperature</b>	215 °C

### Viscosity

<b>Kinematic viscosity</b>	10,386 mm <sup>2</sup> /s at 25 °C
<b>Dynamic viscosity</b>	10,500 cP at 25 °C
<b>Explosive properties</b>	None
<b>Oxidizing properties</b>	None

### 9.2 Other information

<b>Temperature class (USA, acc. to NEC 500)</b>	T3 Maximum permissible surface temperature on the equipment: 200 °C
---	--

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

### 10.5 Incompatible materials

Oxidizers.

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

##### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

##### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
polyethylene glycol (5) undecyl ether	34398-01-1	oral	1,400 mg/kg
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)	55965-84-9	oral	100 mg/kg
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)	55965-84-9	dermal	300 mg/kg
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)	55965-84-9	inhalation: vapor	3 mg/l/4h

##### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

##### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

##### Respiratory or skin sensitization

May cause an allergic skin reaction.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

##### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

##### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

##### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

##### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

### SECTION 12: Ecological information

#### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
distillates (petroleum) hydrotreated, light	64742-47-8	LL50	5 mg/l	fish	96 h
distillates (petroleum) hydrotreated, light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h
polyethylene glycol (5) undecyl ether	34398-01-1	EC50	>1 mg/l	fish	48 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
distillates (petroleum) hydrotreated, light	64742-47-8	LL50	17 mg/l	fish	24 h
distillates (petroleum) hydrotreated, light	64742-47-8	EL50	4.6 mg/l	aquatic invertebrates	24 h
odorless mineral spirits	64742-48-9	EC50	15.41 mg/l	microorganisms	40 h

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Other adverse effects

#### Endocrine disrupting potential

None of the ingredients are listed.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

### SECTION 14: Transport information

- 14.1 UN number** **Not subject to transport regulations**
- 14.2 UN proper shipping name** **Not relevant**
- 14.3 Transport hazard class(es)** None
- 14.4 Packing group** Not relevant
- 14.5 Environmental hazards** Non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user**  
There is no additional information.
- 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code**  
The cargo is not intended to be carried in bulk.
- 14.8 Information for each of the UN Model Regulations**
  - Transport of dangerous goods by road or rail (49 CFR US DOT)**  
Not subject to transport regulations.
  - International Maritime Dangerous Goods Code (IMDG)**  
Not subject to IMDG.
  - International Civil Aviation Organization (ICAO-IATA/DGR)**  
Not subject to ICAO-IATA.

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations specific for the product in question**
  - National regulations (United States)**
    - Superfund Amendment and Reauthorization Act (SARA TITLE III )**
    - The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)**  
none of the ingredients are listed
    - Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)**
    - List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)**  
none of the ingredients are listed
    - Clean Air Act**  
none of the ingredients are listed
    - California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987**  
none of the ingredients are listed
  - Industry or sector specific available guidance(s)**
    - NPCA-HMIS® III**  
Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

Category	Rating	Description
Personal protection	-	

### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
4.1	Following eye contact: Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.	Following eye contact: Remove contact lenses, if present and easy to do. Continue rinsing.	yes
14.1	UN number: Not required Not subject to transport regulations	UN number: Not subject to transport regulations	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

Abbr.	Descriptions of used abbreviations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## A10 Pure Polish

version number GHS 3.0.

revision 2018-09-20.

Code	Text
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.