



Pure Science. Perfect Finish.

TECHNICAL DATA SHEET



Product Name: A4 OEM Compound

Part No.	Size	Unit
A4-32	32 fl oz	12/case
A4-1G	Gallon	4/case

Description:

A4 OEM Compound is a versatile, easy to use abrasive compound that can remove 2000 grit sand scratches, oxidation, and water spots. A4 OEM Compound utilizes a blend of micro-abrasive technology to cut quickly, with very little surface swirling and create a high gloss finish for all types of painted substrates. Easy clean-up with minimal dustiness. Silicone free, no fillers, body shop safe and VOC compliant.

Directions:

Apply A4 OEM Compound to a 2 ft. by 2 ft. area. Buff using appropriate rpm and sufficient pressure, to achieve desired paint correction. Use a wool or aggressive foam pad for maximum cut. Wipe off residue with microfiber or soft towel and desired alcohol based solution.

General Info:

				5-45°C 41-113°F				HS Paint	UHS (SRC) Paint
--	--	--	--	--------------------	--	--	--	-------------	-----------------------

Cautions:

Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Ingestion can cause gastrointestinal irritation. Prolonged skin contact may cause slight irritation.

First Aid:

Eyes: Flush with water for 15 minutes, call physician if irritation persists. Inhalation: Remove to fresh air, call physician if irritation persists. Ingestion: Do not induce vomiting, call physician.

Technical Data:

Flash Point:	>200F (>100.0C)
Appearance:	Pale Purple
Physical State:	Liquid (Viscous)
Odor:	Characteristic
Specific Gravity:	1.038 g/cm ³ 8.655 lbs/USGal (H ₂ O = 1)
Dangerous Goods:	Not Regulated - US DOT, IATA, IMDG