

Product Name:

Directions:

General Info:

Cautions:

First Aid:

Pure Science. Perfect Finish.					
TECHNICAL DATA SHEET					
M12 Full Speed Compound					
Part No. Size	e Unit		UT22	L	
M12-16	16oz	12/Case	C	2	
M12-32	32oz	12/Case		RURE SCORE	
M12-1G	1 Gallon	4/Case			
M12 FULL SPEED COMPOUND is a modern, fast acting, gel coat leveling					
compound designed to remove 800 grit or finer sand scratches. This					
superior formulation provides a high gloss, haze-free finish with easy					
clean-up and very little swirling. Silicone-free and VOC compliant.					
Shake well. Apply product evenly to a 2 ft by 2 ft area. Using a rotary					
polisher with a wool or foam pad, slowly buff using an overlapping					
pattern with enough pressure to eliminate surface defects. As the compound material diminishes, finesse the paint surface - progressively					
using less pressure until a high gloss is achieved.					
		5-45°C		UHS	
	SDS	41-113°F	Silicone	HS (SRC) Paint Paint	
Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Ingestion can cause gastrointestinal irritation. Prolonged skin contact may cause slight irritation.					
Eyes: Flush with water for 15 minutes, call physician if irritation persists. Inhalation: Remove to fresh air, call physician if irritation persists. Ingestion: Do not induce vomiting, call physician.					

Technical Data:

Flash Point:	>200F (>93.3C)
Appearance:	Tan/Light Brown
Physical State:	High viscosity paste
Odor:	Characteristic
Specific Gravity:	1.26g/cm³, 10.50 lb/USGal (H ₂ O = 1)
Dangerous Goods:	Not regulated - US DOT, IATA, IMDG

Puris, LLC 10963 Leroy Drive Northglenn Colorado 80233 (01) 303 252 3800 sales@puris.org www.puris.org