



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

### SECTION 1: Identification

- 1.1 Product identifier**  
**Trade name** D37 Hybrid Polymer Spray Sealant
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**  
**Relevant identified uses** Vehicle paint protectant
- 1.3 Details of the supplier of the safety data sheet**  
B&B Blending, LLC  
10963 Leroy Drive  
Northglenn  
CO 80233  
United States
- telephone  
1.800.875.6320, 1.303.289.6320  
e-mail: info@bbblending.com  
website  
bbblending.com
- e-mail (competent person)** Btirrell@bbblending.com
- 1.4 Emergency telephone number**  
**Emergency information service** USA 1.800.535.5053, INTL 1.352.323.3500  
24 hour emergency number

### SECTION 2: Hazard(s) identification

- 2.1 Classification of the substance or mixture**  
**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

Section	Hazard class	Cat-egory	Hazard class and category	Hazard state-ment
A.7	Reproductive toxicity	2	Repr. 2	H361f

For full text of abbreviations: see SECTION 16

#### The most important adverse physicochemical, human health and environmental effects

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

#### Additional information

Containing a PBT-/vPvB-substance in a concentration of  $\geq 0,1\%$ .

- 2.2 Label elements**  
**Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

**Signal word** Warning

**Pictograms**

**GHS08**



**Hazard statements**

**H361f** Suspected of damaging fertility.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

### Precautionary statements

**P202** Do not handle until all safety precautions have been read and understood.  
**P280** Wear protective gloves/protective clothing/eye protection/face protection.  
**P308+P313** If exposed or concerned: Get medical advice/attention.  
**P405** Store locked up.  
**P501** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazardous ingredients for labelling** Octamethylcyclotetrasiloxane

### 2.3 Other hazards

#### Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture).

### 3.2 Mixtures

#### Description of the mixture

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
odorless mineral spirits	CAS No 64742-48-9	1 - <3	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
octamethylcyclotetrasiloxane	CAS No 556-67-2	1 - <3	Repr. 2 / H361f Flam. Liq. 3 / H226	PBT vPvB
decamethylcyclopentasiloxane	CAS No 541-02-6	0.1 - <1	Flam. Liq. 4 / H227	PBT vPvB

#### Notes

PBT: The substance was identified as a PBT (persistent, bioaccumulative and toxic)  
vPvB: The substance was identified as a vPvB (very persistent and very bioaccumulative)

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

## SECTION 4: First-aid measures

### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray. BC-powder. Carbon dioxide (CO<sub>2</sub>).

#### Unsuitable extinguishing media

Water jet.

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>). Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Remove persons to safety.

#### For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). collect spillage

sawdust

kieselgur (diatomite)

sand

universal binder

#### Appropriate containment techniques

Use of adsorbent materials.

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Recommendations

##### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

##### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Control of the effects

##### Protect against external exposure, such as

Frost.

##### General rule

Do not use for squirting or spraying.

##### Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

#### 7.3 Specific end use(s)

See section 16 for a general overview.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2,000						29 CFR 1910.1000

##### Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97.3 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97.3 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.059 mg/kg	pelagic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	1.7 mg/kg	(top) predators	water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.44 µg/l	aquatic organisms	freshwater	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.044 µg/l	aquatic organisms	marine water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	3 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.3 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.59 mg/kg	benthic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.16 mg/kg	terrestrial organisms	soil	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	benthic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	13 mg/kg	(top) predators	water	short-term (single instance)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	pelagic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.2 µg/l	aquatic organisms	freshwater	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	0.12 µg/l	aquatic organisms	marine water	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.27 mg/kg	terrestrial organisms	soil	short-term (single instance)

### 8.2 Exposure controls

#### Appropriate engineering controls

General ventilation.

#### Individual protection measures (personal protective equipment)

##### Eye/face protection

Wear eye/face protection.

##### Skin protection

##### Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

##### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	Liquid
Color	Green
Odor	Fruity



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

### Other safety parameters

PH (value)	5 – 7 (25 °C)
Melting point/freezing point	Not determined
Initial boiling point and boiling range	100 °C
Flash point	>100 °C at 101.3 kPa
Evaporation rate	Not determined
Flammability (solid, gas)	Not relevant Fluid

### Explosive limits

Lower explosion limit (LEL)	0.7 vol%
Upper explosion limit (UEL)	5.4 vol%
Vapor pressure	31.69 hPa at 25 °C
Density	0.9915 g/ml 8.26 lb/gal
Vapor density	This information is not available
Solubility(ies)	Not determined

### Partition coefficient

- n-octanol/water (log KOW)	This information is not available
Auto-ignition temperature	343 °C

### Viscosity

Kinematic viscosity	7,060 cSt at 25 °C
Dynamic viscosity	7,000 cP at 25 °C
Explosive properties	None
Oxidizing properties	None

### 9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2 Maximum permissible surface temperature on the equipment: 300 °C
--	--



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

#### 10.5 Incompatible materials

Oxidizers.

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

##### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

##### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

##### Acute toxicity

Shall not be classified as acutely toxic.

##### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

##### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

##### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

##### Reproductive toxicity

Suspected of damaging fertility.

##### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

##### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

##### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

### SECTION 12: Ecological information

#### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
octamethylcyclotetrasiloxane	556-67-2	LC50	>22 µg/l	fish	96 h
octamethylcyclotetrasiloxane	556-67-2	EC50	>1,000 mg/l	aquatic invertebrates	96 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	96 h
decamethylcyclopentasiloxane	541-02-6	EC50	>2.9 µg/l	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
odorless mineral spirits	64742-48-9	EC50	15.41 mg/l	microorganisms	40 h
octamethylcyclotetrasiloxane	556-67-2	LC50	10 µg/l	fish	14 d
octamethylcyclotetrasiloxane	556-67-2	EC50	>500 mg/l	aquatic invertebrates	24 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	14 d
decamethylcyclopentasiloxane	541-02-6	EC50	>15 µg/l	aquatic invertebrates	21 d

#### 12.2 Persistence and degradability

Data are not available.

#### 12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

#### 12.6 Other adverse effects

##### Endocrine disrupting potential

The mixture contains substance(s) with an endocrine disrupting potential.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.



##### Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

##### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

<b>14.1 UN number</b>	<b>3082</b>
<b>14.2 UN proper shipping name</b>	<b>Environmentally hazardous substance, liquid, n.o.s.</b>
<b>14.3 Transport hazard class(es) Class</b>	<b>9 Environmentally hazardous</b>
<b>14.4 Packing group</b>	III Substance presenting low danger
<b>14.5 Environmental hazards</b>	Hazardous to the aquatic environment
<b>14.6 Special precautions for user</b>	There is no additional information.
<b>14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code</b>	The cargo is not intended to be carried in bulk.
<b>14.8 Information for each of the UN Model Regulations</b>	
<b>Transport of dangerous goods by road or rail (49 CFR US DOT)</b>	
Not regulated under DOT until packaged in single containers larger than 119 gallons each - liquid, or 882 lbs each - solid.	
<b>Index number</b>	3082
<b>Proper shipping name</b>	Environmentally hazardous substance, liquid, n.o.s.
<b>Particulars in the shipper's declaration</b>	UN3082, Environmentally hazardous substance, liquid, n.o.s., 9, III
<b>Class</b>	9
<b>Packing group</b>	III
<b>Danger label(s)</b>	9 Fish and tree
 	
<b>Environmental hazards</b>	Yes Hazardous to the aquatic environment
<b>Special provisions (SP)</b>	8, 146, 173, 335, IB3, T4, TP1, TP29
<b>ERG No</b>	171



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

### International Maritime Dangerous Goods Code (IMDG)

**UN number** 3082  
**Proper shipping name** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
**Class** 9  
**Marine pollutant** Yes  
Hazardous to the aquatic environment  
**Packing group** III  
**Danger label(s)** 9  
Fish and tree



**Special provisions (SP)** 274, 335, 969  
**Excepted quantities (EQ)** E1  
**Limited quantities (LQ)** 5 L  
**EmS** F-A, S-F  
**Stowage category** A

### International Civil Aviation Organization (ICAO-IATA/DGR)

**UN number** 3082  
**Proper shipping name** Environmentally hazardous substance, liquid, n.o.s.  
**Class** 9  
**Environmental hazards** Yes  
Hazardous to the aquatic environment  
**Packing group** III  
**Danger label(s)** 9  
Fish and tree



**Special provisions (SP)** A97, A158, A197  
**Excepted quantities (EQ)** E1  
**Limited quantities (LQ)** 30 kg

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

**Toxic Substance Control Act (TSCA)** All ingredients are listed

#### Superfund Amendment and Reauthorization Act (SARA TITLE III)

#### The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

#### Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

#### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

#### List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

none of the ingredients are listed

#### Clean Air Act

none of the ingredients are listed



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

#### VOC content

Regulated Volatile Organic Compounds (VOC-EPA). 2.729 %. Regulated Volatile Organic Compounds (VOC-Cal ARB). 2.729 %.

#### Industry or sector specific available guidance(s)

##### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

##### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

##### National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
CA	NDSL	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

##### Legend

DSL Domestic Substances List (DSL)  
NDSL Non-domestic Substances List (NDSL)  
REACH Reg. REACH registered substances  
TSCA Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

### SECTION 16: Other information, including date of preparation or last revision

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		Precautionary statements: change in the listing (table)	yes
9.1	Dynamic viscosity: 7,000 cP	Dynamic viscosity: 7,000 cP at 25 °C	yes
15.1	VOC content: Regulated Volatile Organic Compounds (VOC-EPA). Regulated Volatile Organic Compounds (VOC-Cal ARB).	VOC content: Regulated Volatile Organic Compounds (VOC-EPA). 2.729 %. Regulated Volatile Organic Compounds (VOC-Cal ARB). 2.729 %.	yes
15.1		National inventories: change in the listing (table)	yes

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Asp. Tox.	Aspiration hazard
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ERG No	Emergency Response Guidebook - Number
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## D37 Hybrid Polymer Spray Sealant

version number GHS 2.0.

revision 2019-10-11.

Abbr.	Descriptions of used abbreviations
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.